

Expand your company or school network to another building on your campus so more people can connect.



## Long-range 2.4 GHz Wireless N300 Outdoor Bridge

Includes PoE injector kit for versatile installation

ENS202 is a high-speed, long-range outdoor 802.11n Wireless Bridge that operates on the 2.4 GHz band and is an ideal solution for building-to-building wireless bridging, for stable streaming of video from connected IP security cameras in parking lots or garages back to a company network, or for sending data to outdoor digital signage.

The ENS202 is compliant with the IEEE802.11 b/g/n standards delivering a wireless data rate of up to 300Mbps. It features an internal directional 8 dBi MIMO (Multiple In/Multiple Out) antenna that coupled with its strong transmit power of up to 400mW makes the ENS202 a compelling performance solution for small and growing businesses at a very affordable price. The ENS202 can also be used in other operational modes including as an Access Point. When used as an Access Point it should be positioned in such a way, because of its more focused directional antenna signal array, to offer wireless network connectivity to a more defined outdoor venue rather than a more general outdoor area around it.

ENS202 also features a robust security feature set that includes support for WPA/WPA2 Personal and Enterprise encryption, 802.1x RADIUS authentication, hidden SSID and MAC address filtering.

The ENS202 also features an IP65 rated weatherproof housing that ensures continued operation in harsh outdoor environments or in climates of extreme cold, heat or continuous moisture.

### Key Features

- + 400mW high transmit power enabling long range connectivity
- + Designed for outdoor deployment with IP65 waterproof housing
- + Supports IEEE802.11b/g/n wireless standards with up to 300 Mbps data rate
- + Integrated dual-polarity internal 8 dBi directional MIMO antenna
- + Signal strength LED indicators, pole mount kit, PoE kit provide easy installation
- + Can be monitored after deployment with EnGenius EZ Controller™ software for Windows

## Hardware

RF: 2.4 GHz Frequency Band

Memory: 64MB

Flash: 16MB

## Antenna

Internal 8 dBi Directional Antenna with Dual Polarization

## Physical Interface

2 x RJ-45 Fast Ethernet (10/100 Mbps)

1 x Reset Button

## Power Requirements

- Active Ethernet (Power-over-Ethernet)

- Proprietary PoE design

- Power Adapter (United States) 24V / 0.6A

## RF Specification

Frequency Band

2.4 GHz

IEEE 802.11b/g/n

## Data rate

Up to 300 Mbps

## Software

### Operation Modes

Access Point / Client Bridge / Client Router / WDS

### Wireless/Network

Auto Channel Selection

Distance Control (802.1x Ack timeout)

CLI (Command Line Interface) Supported

802.1x RADIUS Supplicant (CB Mode)

Multiple SSID (4 SSID), BSSID

WDS AP / WDS Bridge / WDS Station

Multicast Supported

VLAN Tagging / VLAN Pass-through

Auto Reboot

Wi-Fi Scheduling

### Security

WPA/WPA2 Personal (WPA-PSK using TKIP or AES)

WPA/WPA2 Enterprise (WPA-EAP using TKIP)

Hide SSID in beacons

MAC address filtering, up to 50 field

Wireless STA (Client) connected list

### QoS (Quality of Service)

WMM (Wireless Multimedia)

## ENVIRONMENT & MECHANICAL

### Temperature Range

Operating -20°C~70°C / -4°F~158°F

Storage -30°C to 80°C / -22°F to 176°F

Humidity (non-condensing)

0% ~ 90% typical

## Weights & Measures

### ENS202 Device

Weight: 0.7 lbs.

Width: 3.9"

Length: 7.3"

Height: 1.14"

### Packaging

Weight: 1.6 lbs.

Width: 2.8"

Length: 12.2"

Height: 9.2"

## Package Contents

- ENS202 Bridge
- Power Adapter
- PoE Injector (EPE1212)
- Pole Mount set
- Screw Set
- Quick Start Guide
- Technical Support Card

